

NORISK

Scan for more info.



Article Slide

Range Terrain

Reference 1225.07

EU Regulation EN ISO 20345:2011 CE

Protection Class S3 SRC WRU

Sizes 39-48 (UK: 6-13)



Description

Slide is a S3 SRC WRU protection class safety shoe recognized mainly for its comfort and resistance. Developed with a water repellent nubuck leather, a breathable lining and an abrasion resistant double density PU sole significantly increasing the overall comfort of the shoe. Foot health and comfort are ensured by the fiberglass toe cap and flexible kevlar midsole making it a 100% metal free product. This product is incorporated Clima Cork System technology which regulates the temperature of the feet.

Safety boot ranging from size 39 to 48, Slide is ideal for construction.

Characteristics

Sole

DOUBLE DENSITY PU

Protective Toe Cap

FIBER GLASS
(impact-resistant up to 200J)

Protective Midsole

KEVLAR (perforation-resistant up to 1100 N)

Upper material

NUBUCK LEATHER
(water repellent)

Lining material

BREATHABLE ORANGE
TEXTILE

Insole

TITAN ANTI-STATIC W/
SHOCK ABSORTION

Weight

655 gr
(average weight for size 42)

Width

11
(normal last)



100 %
Metal free



Clima Cork
System



Shock
Absorber



Anti Slip
Sole



Antistatic



Fuel/oil
Resistant Sole



Water
Repellent

NORISK   

Sol Pinheiro 4810-718 Guimarães - Portugal | Tel: +351 253 776 666 | Email: customers@noriskeurope.com | www.norisk.pt

Language EN

Date july, 2022